



CTM/CTL SERIES

Carbon Treatment Systems

Features:

- Leak-proof
- Choice of Corrosion Resistant in-tank or out-of-tank pumps.
 - Horizontal seal-less centrifugal magnetic pumps
 - Horizontal centrifugal single or double mechanical sealed pumps.
 - Vertical immersible cantilevered seal-less pumps with dry run capability.
- Rugged, All Plastic Construction.
- Reusable polypropylene mesh carbon bags with handle, velcro opening one end.
- CPVC, Polypropylene, PVDF.
- Sulfur Free Activated Free Coconut Based Carbon.



Optional slurry tank for chemical addition, pre-coating, powdered carbon slurry, or pump priming.

Recommended Applications:

Purification of Acid and Alkaline Solutions

Precious Metal Baths and other High Purity Solutions

Sizing your system is made easy using the following formula comparing lbs. per hundred gallon and level of contamination.

Mild contamination

Moderate contamination

Heavy contamination

1-3 lbs. per hundred

4-7 lbs. per hundred gallons

8-10 lbs. per hundred gallons

Flow rate 0.50 gallon per minute per lbs. of carbon

Resident contact time is the essential ingredient for a successful decontamination process. Less is best when adsorbing organic contaminants. Whether choosing the familiar Penguin P series vertical in tank pump, horizontal centrifugal seal-less magnetic drive or mechanical seal style Penguin has the right pump for the right job.

Filter Pump Industries offers complete single or dual chamber systems with slurry tank for the more contaminated baths requiring more holistic and aggressive approach to organic removal. Our slurry tank configuration allows pre-coating of the cartridge media (1-3 micron density) with flocculent producing a very tight filter surface to trap and capture the loose powder carbon.

All Filter Pump systems take into consideration the flow and performance values you expect in a superior product. Penguin has the right treatment system for you. Contact your Filter Pump Industries application engineer for further details.



Filter Pump a Division of Finish Thompson Inc.

CTM/CTL SERIES

Carbon Treatment Systems



System Model	Pump Model	Chamber Model	Carbon Treatment GPM	Capacity Post Filter QTY	Filter Lgth inch	GAC lbs	Ht	Wth	Lth	Wt
CTM-P600	P-3/4A	6CT-6A	250-500	3	6	6	38	18	21	113
CTM-M600	MTD-1/2B	6CT-6A	250-500	3	6	6	38	18	21	113
CTM-P900	P-1/2AK-HP	6CT-9A	450-720	3	9	10	48	18	21	122
CTM-M900	MTD-3/4B	6CT-9A	450-720	3	9	10	48	18	21	122
CTM-P1500	P-1AK	8CT-15A	600-1050	5	10	16	38	20	23	132
CTM-M1500	MTD-1B	8CT-15A	600-1050	5	10	16	38	20	23	132
CTL-P2400	P-11/2AK	12CT-24A	1200-1920	12	6	25	38	28	24	175
CTL-M2400	MTD-11/2B	12CT-24A	1200-1920	12	6	25	38	28	24	175
CTL-P3600	P-2AK	12CT-36A	1800-2520	12	10	36	48	28	24	240
CTL-M3600	MTD-2B	12CT-36A	1800-2520	12	10	36	48	28	24	240
CTL-P4800	P-2AK	2-12CT-24A	1800-2880	24	6	50	38	32	48	360
CTL-M4800	MTD-2B	2-12CT-24A	1800-2880	24	6	50	38	32	48	360
CTL-P7200	P-2AK	2-12CT-36A	2700-3400	24	10	72	48	32	48	450
CTL-M7200	MTD-2B	2-12CT-36A	2700-3400	24	10	72	48	32	48	450



Filter Pump a Division of Finish Thompson Inc.